



J26 maxi



Flint Lighter

Guard

Child-resistant feature; stainless steel.

Hood

Windshield; steel.

Flint

Supplies material for spark; misch metal.

Flint spring

Feeds flint onto spark wheel as flint wears; spring steel.

Spark wheel subassembly

Spark wheel

Generates spark from flint; serrated hardened steel wire.

Cheeks

Turn spark wheel; zinc alloy.

Fork / Pusher subassembly

Pusher

Pad for depressing fork to activate valve; polyamide.

Fork

Lifts jet allowing fuel release; zinc alloy.

Fork spring

Returns jet automatically to shut off position; spring steel.

Jet / Globe seal subassembly

Jet

Moving part of valve which opens and closes fuel flow; zinc alloy.

Elastomer globe seal

Seals valve in closed position, shuts off fuel; synthetic rubber.

Fixed flame valve subassembly

Valve body

Body of the fixed flame valve, aluminium.

Membrane

Regulates fuel flow; polypropylene microporous membrane.

Disk

Seals membrane in valve; aluminium.

Fuel

Isobutane blend hydrocarbon.

Body

Contains the fuel; polyacetal, Delrin®.

Base

Seals in fuel supply; polyacetal, Delrin®.

Ball

Seals fuel port after filling; carbide steel.

8.9ml = 3000